

DC AXIAL FANS



DAKA[®] SERIES 120×120×38 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 5 Blades
- * Rotational direction CCW view from front face
- * Weight: 256g (9.03 OZ)

MODEL

Bearing Type

Rated Voltage

Operating Voltage Range

Rated Current

Rated Input Power

Speed

Maximum Air Flow

Maximum Air Pressure

Acoustic Noise

Life expectancy
L₁₀@40°C

PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DAKA1238_12E	FG	B	12	5.0 to 13.2	0.4	4.8	2100	2.515	88.77	3.59	0.141	33.89	70000
DAKA1238_12L	FG	B	12	5.0 to 13.2	0.5	6	2600	3.133	110.59	5.64	0.222	40.23	70000
DAKA1238_12M	FG	B	12	5.0 to 13.2	0.8	9.6	3200	3.866	136.44	9.27	0.365	46.30	70000
* DAKA1238_12H	FG	B	12	5.0 to 13.2	1.5	18	3900	4.752	167.73	14.20	0.559	52.55	70000
DAKA1238_12U	FG	B	12	5.0 to 13.2	2.5	30	4800	5.875	207.37	21.20	0.835	57.80	70000

