

DC AXIAL FANS

DAKA SERIES 60×60×25 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 74g (2.61 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DAKA0625_12E	FG	B	12	5.0 to 13.2	0.4	4.8	3600	0.590	20.82	4.36	0.172	28.05	70000
DAKA0625_12L	FG	B	12	5.0 to 13.2	0.5	6.0	4400	0.740	26.11	6.57	0.259	33.55	70000
DAKA0625_12M	FG	B	12	5.0 to 13.2	0.6	7.2	5200	0.845	29.82	9.02	0.355	38.81	70000
* DAKA0625_12H	FG	B	12	5.0 to 13.2	0.7	8.4	6000	1.009	35.60	12.06	0.475	43.66	70000
DAKA0625_12U	FG	B	12	5.0 to 13.2	0.8	9.6	7000	1.166	41.14	15.80	0.622	47.21	70000
DAKA0625_12S	FG	B	12	5.0 to 13.2	1.0	12.0	8000	1.342	47.38	20.40	0.801	50.61	70000
DAKA0625_12F	FG	B	12	5.0 to 13.2	1.2	14.4	9000	1.506	53.17	24.90	0.980	55.81	70000

