

DC AXIAL FANS

2B SERIES 60×60×38 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 116g (4.09 OZ)



MODEL	Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
2B06038_12L	-FG / RD	B	12	7.0 to 13.2	0.6	7.2	8000	1.297	45.80	22.00	0.87	51.5	110000
2B06038_12M	-FG / RD	B	12	7.0 to 13.2	0.8	9.6	9000	1.471	51.95	27.60	1.09	54.0	90000
2B06038_12H	-FG / RD	B	12	7.0 to 13.2	0.96	11.52	10000	1.637	57.80	34.50	1.36	57.0	70000
2B06038_12U	-FG / RD	B	12	7.0 to 13.2	1.15	13.8	11000	1.786	63.06	40.10	1.579	59.5	70000
2B06038_12S	-FG / RD	B	12	7.0 to 13.2	1.5	18	12000	1.984	70.06	49.80	1.96	61.5	70000
* 2B06038_12G	-FG / RD	B	12	7.0 to 13.2	1.8	21.6	13500	2.050	72.41	60.60	2.386	64.6	70000

