

DC AXIAL FANS



DAKA SERIES 40×40×10 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #26 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 16.55g (0.584 OZ)

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours	
DAKA0410_12E	-FG / RD	B	12	5.0 to 13.2	0.07	0.84	4600	0.153	5.39	2.29	0.090	21.27	70000	
DAKA0410_12L	-FG / RD	B	12	5.0 to 13.2	0.09	1.08	5400	0.196	6.93	3.15	0.336	24.08	70000	
DAKA0410_12M	-FG / RD	B	12	5.0 to 13.2	0.11	1.32	6200	0.219	7.8	4.17	0.481	28.01	70000	
* DAKA0410_12H	-FG / RD	B	12	5.0 to 13.2	0.14	1.68	7000	0.252	8.96	5.32	0.677	31.25	70000	
DAKA0410_12U	-FG / RD	B	12	5.0 to 13.2	0.17	2.04	8000	0.296	10.37	6.79	0.481	35.16	70000	

