



DC AXIAL FANS

DS SERIES 60×60×25 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #26 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 55g (1.940 OZ)

MODEL		Bearing Type		Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40 °C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours	
DS06025_12X	-FG	B	R	12	7.0 to 13.2	0.10	1.20	2000	0.309	10.92	1.38	0.054	18.1	70000
DS06025_12E	-FG	B	R	12	7.0 to 13.2	0.20	2.40	2500	0.387	13.65	2.16	0.085	20.6	70000
DS06025_12L	-FG	B	R	12	7.0 to 13.2	0.30	3.60	3300	0.551	18.45	3.62	0.143	26.0	70000
DS06025_12L	-FG	B	R	12	7.0 to 13.2	0.40	4.80	4000	0.673	23.76	5.21	0.205	31.5	70000
DS06025_12H	-FG	B	R	12	7.0 to 13.2	0.60	7.20	5000	0.808	28.54	8.01	0.315	37.4	70000
* DS06025_12U	-FG	B	R	12	7.0 to 13.2	0.70	8.40	6800	1.101	38.85	12.54	0.494	45.9	70000

