

DC AXIAL FANS

DS SERIES
80×80×25 mm 12v,24v

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CCW view from front face
- * Weight: 68g (2.4 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours	
DS08025_12L	-FG/RD	B I B	12	7.0 to 13.2	0.15	1.80	2050	0.831	29.34	2.10	0.083	24.9	70000	
DS08025_12M	-FG/RD	B I B	12	7.0 to 13.2	0.23	2.76	2450	1.016	35.89	2.88	0.113	29.6	70000	
DS08025_12H	-FG/RD	B I B	12	7.0 to 13.2	0.30	3.60	3000	1.246	44.02	4.43	0.174	34.5	70000	
* DS08025_12U	-FG/RD	B I B	12	7.0 to 13.2	0.70	8.40	4500	1.824	64.44	9.73	0.383	46.0	70000	
DS08025_24H	-FG/RD	B	24	10.0 to 26.4	7.20	7.20	3000	1.246	44.02	4.43	0.174	34.5	70000	

