

DC AXIAL FANS

DV SERIES 40×40×28 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1061 AWG #26 or Equivalent
- * Impeller: 5 Blades
- * Rotational direction CCW view from front face
- * Weight: 40g (1.41 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
DV04028_12E	-FG / RD	B	12	7.0 to 13.2	0.10	1.20	8000	0.261	9.20	9.30	0.366	31.3	120000
DV04028_12L	-FG / RD	B	12	7.0 to 13.2	0.15	1.80	10000	0.340	12.00	14.60	0.575	36.5	120000
DV04028_12M	-FG / RD	B	12	7.0 to 13.2	0.20	2.40	12000	0.408	14.40	20.31	0.800	41.3	120000
DV04028_12H	-FG / RD	B	12	7.0 to 13.2	0.30	3.60	14000	0.481	17.00	27.60	1.087	45.4	110000
* DV04028_12U	-FG / RD	B	12	7.0 to 13.2	0.46	5.52	16500	0.581	20.50	37.30	1.469	48.8	100000

