

DC AXIAL FANS

DY SERIES 70×70×25 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 9 Blades
- * Rotational direction CCW view from front face
- * Weight :75g (2.645 OZ)



MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
F7025_12EX	FG	B	12	10.8 to 13.2	0.20	2.40	2800	0.721	25.46	3.49	0.137	27.9	70000
F7025_12LX	FG	B	12	10.8 to 13.2	0.25	3.00	3600	0.902	31.85	5.30	0.209	32.2	70000
F7025_12MX	FG	B	12	10.8 to 13.2	0.35	4.20	4200	1.077	38.01	7.58	0.298	38.8	70000
F7025_12HX	FG	B	12	10.8 to 13.2	0.70	8.40	5200	1.481	52.29	11.32	0.446	43.6	70000

*P & Q CURVE (AT RATED VOLTAGE):

